

PP 6535

PRINTABLE CARTON SEALING TAPE

MEDIUM TO HEAVY DUTY GRADE

TECHNICAL SHEET


TYPICAL APPLICATIONS

- Easy direct printable BOPP carton sealing tape.
- Medium to heavy weight carton sealing tape.
- Suitable for manual or automated usage.



ADVANTAGES AND BENEFITS

- Directly printable with polyamide inks (no need of prymer and release).
- Excellent adhesion even on recycled cartons.
- Excellent aggressive tack.
- High holding power adhesive. It guarantees a long-lasting adhesion and a safe storage even with temperature variations.



CONSTRUCTION

- Backing: biaxially oriented polypropylene clear film.
- Adhesive: Synthetic rubber and hydrocarbon resins.
- Extra adhesive weight to ensure application on difficult rough surfaces.
- Color: Clear, white or brown adhesive.



TECHNICAL DATA

PP 6535	METRIC	US customary system	TEST METHOD
Film Thickness	35 Micron	1,37 mil	AFERA 5006
Total Thickness	55 Micron	2,3 mil	AFERA 5006
Peel Adhesion	5,7 N/cm	53,0 oz/inch	AFERA 5001
Tensile Strength	47 N/cm	26,8 lbf/inch	AFERA 5004
Elongation at break	180 %	180 %	AFERA 5004
Application Temperature	6°C to 45°C	43°F to 113°F	-
Service Temperature	-20°C to 60°C	0°F to 140°F	-



Physical and performance characteristics shown above are obtained following tests recommended by AFERA. The TDS values, are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please maintain the full digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.