



tesa[®] 4313 PV10



Product Information

Premium Packaging Tape with Paper from Sustainable Sources

Product Description

tesa[®] 4313 PV10 is a premium packaging tape featuring a paper backing with a silicone-free release coat and a solvent-free synthetic rubber adhesive system. The tear-resistant premium paper backing is made with paper from well-managed certified forests and other controlled sources. The backing is based on paper, a natural, sustainable material. tesa 4313 PV10 can be used manually or with a dispensing machine and is available in the colors brown and white.

Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

Product Features

- For light to medium weight packages
- Robust specialty paper gives enhanced tear resistance
- High tack adhesive enables a fast closing process
- Suitable for automated application
- Very good printability

Application Fields

- Ideal for sealing of light- and medium-weight cartons
- This paper packaging tape can be used for brand showcasing and advertisement purposes
- Suitable for automated dispensing processes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Backing | Paper | • Total thickness | 107 µm |
| • Type of adhesive | synthetic rubber | | |

Product Assortment

- | | |
|--------------------|--------------|
| • Available colors | white, brown |
|--------------------|--------------|

For latest information on this product please visit <http://l.tesa.com/?ip=04313>



tesa[®] 4313 PV10

Product Information

Properties/Performance Values

• Elongation at break	6 %	• Hand tearability	very good
• Tensile strength	60 N/cm	• Low noise unwinding	yes
• Automatic application	yes	• Packaging Weight	Up to 15 kg

Adhesion to Values

• Steel	7.5 N/cm
---------	----------

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04313>