

## TAMPER EVIDENT TAPE

### PRODUCT DESCRIPTION

Anti-tampering tape with solvent-free water-based acrylic adhesive. Suitable to report any tampering of the packaging. In case of removal, it clearly highlights the attempt to open, leaving a visible message, even if you try to close the package. Possibility of customization: color, print and signaling message.



### FEATURES



No noise unwinding



Solvent free



Flexo printing

### MAIN APPLICATIONS



Anti-tampering



Industries of luxury goods, logistics services, fashion, etc.



Medium weight box sealing

### BACKING MATERIAL

BIAXIALLY ORIENTED POLYESTER

### AVAILABLE VERSIONS

### COLOURS



ORANGE - RED



PANTONE  
ON REQUEST

### TYPE OF ADHESIVE

WATER BASED ACRYLIC

TECHNICAL DATA	Metric	Value	Test Method
Backing thickness	µm	23	AFERA 5006
Total thickness	µm	47	AFERA 5006
Adhesion to steel	N/cm	n.d.	AFERA 5001
Tensile strength	N/cm	50	AFERA 5004
Elongation at break	%	140	AFERA 5004

#### Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Expotape declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.01\_01/03/2023

